



CP-q6 Plus

80mm width w/Auto-Cutter

300mm/sec print speed

The New Thermal Printer Caters To the Needs of All Business



Restaurant
Auto System

1. A look that drives envy

CP-Q6 Plus is a fashioned printer with streamlined and state-of-the-art design, which is helpful to enhance your image and space-saving of your applications. It is a good printer which combine the user-friendly solution and new technology at convergence.



EasyPos
System

2. Excellent performances

CP-Q6 Plus printer positioned for performance-concerned market, it richly features the power functions of 300mm print speed, 4MB memory, supports page mode printing method.



MobilePos
System

3. User-friendly devices with simple, intuitive Besides the powerful function, the CP-Q6 Plus with lots of user-friendly devices as below:

- Beeper and light alarm
- Lighting alarm warning for backorder reminder
- wall mounting hook hole
- support 58mm paper printing by optional divider

4. There is more...

- a. Support QR code and PDF-417
- b. Blackmark and photoelectric sensors built-in

Ordering Information:

CP-Q6 Plus: 80mm thermal printer, w/Auto Cutter, 4MB memory, 300mm print speed., RS232 + USB + LAN





Thermal Receipt Printer



Model	CP-Q6 Plus
Printing method	Direct thermal
Print width	72mm
Column capacity	576 dots/line or 512 dots/line
Printing speed	300mm/s Max.
Interface	USB + Bluetooth
Printing paper	79.5±0.5mm x ø80mm
Line spacing	3.75mm (Adjustable by commands)
Print command	ESC/POS
Column number	80mm paper: Front A - 42 columns or 48 columns/ Front B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A: 12x24 dots Font B: 9x17 dots Simplified/Traditional Chinese: 24x24 dots
Graphics	Monochrome BMP files can be downloaded to FLASH
Sensors	1. Black mark sensor 2. Photoelectric sensor
Beeper and light alarm	Support (Optional)
Cutter	
Auto cutter	Partial
Barcode Character	
Extension character sheet	PC347(Standard Europe)/Katakana/PC850(Multilingual)/PC860(Portuese)/ PC863(Canadian-French)/PC865(Nordic)/West Europe/Greek/Hebrew/East Europe/ Iran/WPC1252/PC886(Cyrillic#2)/PC852(Latin2)/PC858/Iran/Latvian/Arabic/PT151(1251)
1D code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D code	QR CODE / PDF417
Barcode Character	
Input buffer	4096 Kbytes
NV Flash	256 Kbytes
Power	
Power adaptor	Input: AC 100-240V/50~60Hz; Output: DC 24V/2.5A
Power Input	Input: DC24V/2.5A
Cash drawer output	DC 24V/1A
Physical Characteristics	
Weight	1.01 KG
Dimensions	193.76 (D) * 144.23 (W) * 133 (H) mm
Environmental Requirements	
Work environment	Temperature (0~45°C) Humidity (10~80%) (non-condensing)
Storage environment	Temperature (-10~60°C) Humidity (10~90%)
Reliability	
Cutter life	1.5 million cuts
Print head life	150KM
Driver	Win 9X/ Win2000/ Win 2003/ Win XP/ Win 7/ Win8/ Win 10/ Linux